



|  |  |            |
|--|--|------------|
| Portable printer   | MODEL: UDY58B  | 58mm paper |
| <b>Feature:</b>  | <b>Application:</b>  |            |
| <ul style="list-style-type: none"> <li>★ Portable suited for outdoor usage</li> <li>★ Black mark paper location sensor</li> <li>★ battery indicator(7.4V,2600mAh)</li> <li>★ <b>Type C USB</b> port easy to use</li> <li>★ Vairous interface and capabilites</li> <li>★ <b>battery power indicator</b></li> <li>★ High printing speed , up to 90mm/s.</li> </ul> | <ul style="list-style-type: none"> <li>★ Medical Equipment</li> <li>★ Mobile POS/Retail</li> <li>★ Hospitality</li> <li>★ Packing citation</li> <li>★ Deliveries</li> <li>★ Onboard Transportation</li> <li>★ Field reports/Installation</li> <li>★ Warehouse/ logistics</li> <li>★ Utility billing/meter reading</li> </ul> |            |
| Dimension  | 120*80*50mm (W*D*H)  |            |
| Print method   | Line thermal printer   |            |
| Paper width  | 58mm   |            |
| print width  | 48mm   |            |
| Weight ( g)  | 193g   |            |
| Max diameter of paper roll   | 40mm   |            |
| Dot per lie  | 384 dots/line  |            |
| Print speed  | 90mm/s   |            |
| Life cycle time  | 50km(printing density under 12.5%)/100 million pulses  |            |
| text and graphic Support   | English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode<br>(CODE39EAN13EAN8<br>CODABARCODE128CODE93ITF)   |            |
| Dot pitch (resolution)   | 203DPI/8 dots/mm   |            |
| interface  | <b>type C USB</b><br>bluetooth support: Android+IOS  |            |
| Power  | 7.4V rechargeable Lithium battery  |            |

|                      |   |
|----------------------|---|
| Recharge adapter     | Stand by recharging / AC adapter                        |
| Self-check           | Without paper /low power/ cover open                    |
| Black mark test      | Supported   |
| commands             | ESC/POS compatible with order sets                      |
| Paper cut            | By hands  |
| Operate setting      | Android/Windows   |
| Recharge Setting     | Temperature:5°C~40°C;<br>Humidity:20%~85%               |
| Storage Setting      | Temperature:-20°C~70°C;                                 |
| Standard accessories | Long-term preservable paper, AC adapter, li-ion battery |
| Optional accessories | Serial interface cable / leather coat                   |



*[Udyamasoftware.com](http://Udyamasoftware.com)*