

Applications

- PC/Network Security
- Time and Attendance
- Smart Card Application
- AFIS
- Health & Medical
- UIDAI
- Jeevan Pramaan
- AEBAS
- Skill Development
- NREGA
- PDS



Features



Plug & Play USB 2.0 with
High Speed Interface



Lower FAR and FRR



STQC Certified Product



Supports Windows
Operating Systems



Supports Android
Operating Systems



Supports Linux
Operating Systems

Single IRIS Sensor

MIS100 V2

MIS100V2 is high quality USB IRIS Sensor for IRIS Authentication to access desktop or network security. Single IRIS Sensor MIS100V2 can be used extensively for identity applications like Aadhaar Authentication, Banking Applications and Access Control Applications. MIS100V2 quality algorithm can easily identify poor quality IRIS images and can be adjusted easily based on inbuilt LED indications. MIS100V2 works on proprietary distance sensing and focus analysis technology which gives it fast auto capture capabilities.



At a Glance

Sensor Characteristics

Parameters	Specification
Spatial Resolution	: > 50% @ 1.0 LP/mm
Pixel Resolution	: > 10 pixels/mm
Image Margins Left & Right	: >= 0.6x IRIS radius
Top & Bottom	: >= 0.2x IRIS radius
Imaging Wavelength	: 700-900 nm
Pixel Depth	: 8 bits/pixel
Output Image	: KIND1 to KIND7 with JPEG2000 Compression
Capture Mode	: Auto Capture with Built-in Quality Check
Capture Time	: < 2 sec
Safety	: Exempt Group per IEC 62471:2006-07
Health-Safety	: RoHS Compliant
ESD	: Air Discharge+-8 KV, Contact Type +-4Kv
Radiated Emission	: FCC part15B/IEC:CISPR 22 Class B Standard
Radiated Immunity	: As per IEC/EN 61000-4 3:2006+A2:2010
Connectivity	: USB 2.0
Operating System Supports	: Windows XP, Win7, Win2008, Android, Linux, Embedded Linux