

ePayPOS600



Android, iOS, Windows Mobile



Micro USB
BR/EDR V3.0 + BLE4.2



MSR + IC + NFC



High-Capacity Battery



Retail



Supermarket



Restaurant



Hotel



Parking lot



Gas station

ePayPOS600

Operating System	RTOS
Processor	32-bit RISC Core
Memory	RAM: 128KB + ROM:4MB
Bluetooth	BT4.2 (BR/EDR+BLE)
Display	1.4 inch, 128*64, Mono
NFC	13.56MHz, ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare card
Magnetic Card Reader	ISO/IEC 7811, ISO/IEC 7813, Track 1/2/3, Bi-directional swiping
IC Card Reader	ISO/IEC 7816, Conform to EMV L1/L2
Keys / Buttons	5*3 PIN pad 15 keys
Audio	Buzzer
Battery	3.7V/500mAh (optional: 300mAh)
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/1.0A
Peripheral Ports	Micro USB 2.0
Physical	113.6mm (L)*59mm (W)*14mm (H)
Weight	80g
Environment	Operating Temperature: 0°C ~ 45°C (32°F~113°F) Storage Temperature: -10°C ~ 60°C (14°F~140°F) Relative Humidity: 5%-96% (Non-Condensing)
Accessories	USB Cable(only charging)*1, Manual*1
Certifications	PCI, EMV L1&L2, EMV Contactless L1, PayWave, Paypass, Amex, Discover, JCB, Pure, qUICS, Rupay, MIR, TQM, CE, FCC, BIS, ANRT, WPC, PBOC3.0 L1&CL2, PBOC3.0 CL1,DGM, UN38.3, MSDS